

# Technical Section

## Cable Attributes

Overview	655
Oil Resistance	656
Flame Resistance	657
Mechanical Resistance	658
Motion Level	659
Flex Life Testing Parameters	660

<b>Lead Free &amp; RoHS Designation</b>	<b>661</b>
---	------------

<b>European Cable Stranding</b>	<b>662</b>
---------------------------------	------------

<b>Stranded Conductors- AWG</b>	<b>663</b>
---------------------------------	------------

<b>Solid Conductors- AWG</b>	<b>664</b>
------------------------------	------------

<b>Cabling Techniques</b>	<b>665</b>
---------------------------	------------

<b>Typical Motions for Flexing Cables</b>	<b>666</b>
---	------------

<b>National Electrical Code Allowable Conductor Ampacity</b>	<b>667</b>
--	------------

<b>Properties of Insulation Materials</b>	<b>668</b>
---	------------

<b>Cable Recommendations for 100 Common Oils &amp; Coolants</b>	<b>670</b>
---	------------

<b>Number Codes</b>	<b>672</b>
---------------------	------------

Charts 1, 2, 3

## Color Codes

Charts 4 & 5	673
Charts 6 & 7	674
Charts 8 & 9	675
Chart 10	676
Chart 11 & 12	677

<b>Installation Instructions for Cable Track</b>	<b>678</b>
--	------------

<b>North American Regulatory &amp; Safety Standards Agencies</b>	<b>679</b>
--	------------

<b>ER- Exposed Run Approval</b>	<b>681</b>
---------------------------------	------------

# Technical Section

<b>International Regulatory Agencies</b>	<b>682</b>
<b>VFD Cable Selection Guide</b>	<b>684</b>
<b>Voltage Designations</b>	<b>685</b>
<b>ATEX</b>	<b>686</b>
<b>EPIC® Overview</b>	<b>687</b>
<b>How to Choose Connector Housings</b>	<b>688</b>
<b>Plug &amp; Receptacle Overview</b>	<b>689</b>
<b>General Approvals/ Design Specifications</b>	<b>690</b>
<b>PG to Metric Conversion</b>	<b>691</b>
<b>IP Ratings</b>	<b>692</b>
<b>NEMA Ratings</b>	<b>693</b>
<b>Connector Materials</b>	<b>694</b>
<b>Sealing Materials</b>	<b>695</b>
<b>Chemical, Thermal &amp; Mechanical Values</b>	<b>695</b>
<b>Derating Curves</b>	<b>696</b>
<b>Cable Outer Diameter for PG</b>	<b>696</b>
<b>Recommended Torque for EPIC® Assembly Screws</b>	<b>697</b>
<b>Cross Reference for AWG (American Wire Gauge) to mm<sup>2</sup></b>	<b>697</b>
<b>PG Gland Sizes for Multi-Wire Cables</b>	<b>698</b>
<b>Glossary of Terms</b>	<b>699</b>
<b>Conversion Factors</b>	<b>706</b>