

SKINTOP® MS-M ATEX BRUSH

Safe. Protected. Shielded.

NEW



LAPP products are available from
MARYLAND METRICS

P.O. Box 261 Owings Mills, MD 21117 USA
ph:(410)358-3130 (800)638-1830
fx:(410)358-3142 (800)872-9329
RFQ form: <http://mdmetric.com/rfq.htm>

Lapp Index Page: <http://mdmetric.com/elect/contents.htm>



LAPP GROUP

Cable glands

SKINTOP® cable glands nickel plated brass metric

SKINTOP® explosion proof

SKINTOP® MS-M ATEX BRUSH



SKINTOP® MS-M ATEX BRUSH

SKINDICHT® SHVE-M ATEX

Benefits

- Faster and less complicated assembling than any other system
- Optimal low-resistance 360° screen contact
- Easy adjustment of installed cable
- Easy disassembling
- Anti static, cold impact resistant and safe

Application range

- For EMC compliant earthing of the copper braiding and copper shaft sheath
- Chemical and petrochemical industry
- Plant engineering
- Equipment group II / Category 2G+1D

- Devices, machines of type of protection enhanced safety "e"

Approvals (Norm references)



Design

- Metric connection thread acc. to EN 50262

Note

- Type SKINDICHT® SHVE-M ATEX with earthing sleeve for clamping of smaller cable diameters

Technical data

Caution
Installation dimensions and tightening torques see instruction leaflet

Note
SKINDICHT® SHVE-M ATEX
IBExU08ATEX1161 X
Ex II 2G Ex e II
Ex II 1D Ex tD A20 IP 6X
SKINTOP® MS-M ATEX BRUSH
IBExU01ATEX1041 X
Ex II 2G Ex e II
Ex II 1D tD A20 IP6X

Material
SKINTOP® MS-M ATEX BRUSH
Body: nickel plated brass
Insert: special polyamide
EMV-Brush: brass
Seal: special elastomer
O-Ring: special elastomer
SKINDICHT® SHVE-M ATEX
Body: nickel plated brass
Earthing sleeve: brass
Seal: special elastomer
O-Ring: special elastomer

Tests
DIN EN 60079-0
DIN EN 60079-7

Degree of protection
IP 68 - 10 bar

Range of temperature
SKINTOP® MS-M ATEX BRUSH
-30°C up to +90°C
SKINDICHT® SHVE-M ATEX
-20°C up to +80°C

Part number	Part designation / size	Outer-Ø mm from - to	Minimum Ø above braiding in mm	SW mm	Thread length D mm	Pieces / PU
SKINDICHT® SHVE-M ATEX						
52107102	20 x 1,5	6,9-8,9	5.0	24	6.0	10
SKINTOP® MS-M ATEX BRUSH						
52110023	25 x 1,5	9,0-17,0	6.0	29	8.0	10
52110024	32 x 1,5	11,0-21,0	8.0	36	9.0	1
52110025	40 x 1,5	19,0-28,0	10.0	45	9.0	1
52110026	50 x 1,5	27,0-35,0	14.0	54	10.0	1
52110027	63 x 1,5	34,0-45,0	20.0	67	15.0	1
52110028	63 x 1,5 plus	44,0-55,0	25.0	75	15.0	1

U.I. Lapp GmbH

Schulze-Delitzsch-Straße 25 · D-70565 Stuttgart
Tel.: 0711/7838 - 01 · Fax: 0711/7838 - 2640