









High performance steel anchors

R264 - article/Anchor type	Dimensions	6 x 25 H
88549 FNA II-H 	d_0	6
	t_{cd}	35
	h_{ef}	25
	l	54
	inner \varnothing hook	10
	opening dimension of the fastening	6.5
	building materials	BN, VD

R264 - article/Anchor type	Dimensions	6 x 25 OE
88548 FNA II-OE  	d_0	6
	t_{cd}	35
	h_{ef}	25
	l	54
	inner \varnothing eye	10
	building materials	BN, VD

R264 - article/Anchor type	Dimensions	8	10	12
88531 MR 	d_0	8	10	12
	t_{cd}	70	85	100
	h_{ef}	40	50	60
	l	70	85	100
	t_{fix}	22	24	27
	wrench size	13	15	18
	thread	M 8	M 10	M 12
	building materials	BN		

R264 - article/Anchor type	Dimensions	M 6	M 8	M 10
88513 FHY   Approval only valid for zinc plated steel. VdS approval starting from M8.	d_0	10	12	16
	t	50	60	65
	h_{ef}	30	35	40
	l	37	43	52
	thread	M 6	M 8	M 10
	e_2	37	43	52
	e_1	45	55	60
	building materials	BN		

Key → TI-116, building materials → TI-109