






Long-shaft anchors/frame fixings/adjustment fixings

R264 - article/Plug type	Dimensions	8 x 80	8 x 100	8 x 120	10 x 80	10 x 100	10 x 115
88564 FUR-SS 	d_0	8	8	8	10	10	10
	t_d	90	110	130	90	110	125
	h_{ef}	70	70	70	70	70	70
	l	80	100	120	80	100	115
	t_{fix}	10	30	50	10	30	45
	$d_s \times l_s$	6 x 85	6 x 105	6 x 125	7 x 85	7 x 105	7 x 120
	wrench size	10	10	10	13	13	13
	building materials	BN, VD, LD					
	Dimensions	10 x 135	10 x 160	10 x 185	10 x 200	10 x 230	
	d_0	10	10	10	10	10	
t_d	145	170	195	210	240		
h_{ef}	70	70	70	70	70		
l	135	160	185	200	230		
t_{fix}	65	90	115	130	160		
$d_s \times l_s$	7 x 140	7 x 165	7 x 190	7 x 205	7 x 235		
wrench size	13	13	13	13	13		
building materials	BN, VD, LD						

R264 - article/Plug type	Dimensions	10 x 80	10 x 100	10 x 120	10 x 140	10 x 160	10 x 180
88504 SXS-T 	d_0	10	10	10	10	10	10
	t_d	90	110	130	150	170	190
	h_{ef}	50	50	50	50	50	50
	l	80	100	120	140	160	180
	t_{fix}	30	50	70	90	110	130
	$d_s \times l_s$	7.6 x 89	7.6 x 109	7.6 x 129	7.6 x 147	7.6 x 167	7.6 x 187
	drive	T40	T40	T40	T40	T40	T40
	building materials	BN, VD, VP, HP					

R264 - article/Plug type	Dimensions	10 x 60	10 x 80	10 x 100	10 x 120	10 x 140	10 x 160	10 x 180
88504 SXS-F US 	d_0	10	10	10	10	10	10	10
	t_d	70	90	110	130	150	170	190
	h_{ef}	50	50	50	50	50	50	50
	l	60	80	100	120	140	160	180
	t_{fix}	10	30	50	70	90	110	130
	$d_s \times l_s$	7.6 x 69	7.6 x 89	7.6 x 109	7.6 x 129	7.6 x 147	7.6 x 167	7.6 x 187
	drive	T40	T40	T40	T40	T40	T40	T40
	wrench size	13	13	13	13	13	13	13
	building materials	BN, VD, VP, HP						