


MULTI-MONTI




Types, dimensions



Note: When inquiring about 5 digit part numbers beginning with 8, please preface the number with R264-. Example: 88111 should be R264-88111.

R264 - article/MULTI-MONTI type

88903
Type St
Metric stud






$\varnothing \times l$ [mm]	Wrench size hexagon	Connection Thread	Drill \varnothing d_0 [mm]	Drill depth h_1 [mm]	Anchor depth h_{nom} [mm]	Clamping strength t_{fix} [mm]	Admissible tension load in cracked concrete C20/25 [kN]	Admissible tension load in non-cracked concrete C20/25 [kN]	Recommended tension load in uncracked concrete C20/25 ⁴⁾ [kN]
6 x 60	10	M 6x5	5	55	45	15	0.3 ²⁾	1.5 ²⁾	3.8
7.5 x 70	10	M 8x14	6	55	45	25	0.5 ²⁾	2.0 ²⁾	3.7
7.5 x 80	10	M 8x14	6	65	55	25	2.0 ³⁾	3.1 ³⁾	5.3
7.5 x 100	10	M 8x14	6	65	55	45	2.0 ³⁾	3.1 ³⁾	5.3
7.5 x 120	10	M 8x14	6	65	55	65	2.0 ³⁾	3.1 ³⁾	5.3
7.5 x 140	10	M 8x14	6	65	55	85	2.0 ³⁾	3.1 ³⁾	5.3
7.5 x 160	10	M 8x14	6	65	55	105	2.0 ³⁾	3.1 ³⁾	5.3
10 x 80	13	M 10x11	8	65	55	25	0.8 ²⁾	-	5.0
10 x 100	13	M 10x11	8	75	65	35	3.7 ³⁾	4.9 ³⁾	6.8
10 x 120	13	M 10x11	8	75	65	55	3.7 ³⁾	4.9 ³⁾	6.8
10 x 140	13	M 10x11	8	75	65	75	3.7 ³⁾	4.9 ³⁾	6.8
10 x 160	13	M 10x11	8	75	65	95	3.7 ³⁾	4.9 ³⁾	6.8

1) = not a component of the approvals 2) = in acc. with DIBt approval no. Z-21.1-1503 3) = in acc. with ETA 05/0010 4) = manufacturer specification for use without approval

R264 - article/MULTI-MONTI type

88908
Type P
Pan head



$\varnothing \times l$	Hexalobular socket size (TORX)	Head \varnothing [mm]	Drill \varnothing d_0 [mm]	Drill depth h_1 [mm]	Anchor depth h_{nom} [mm]	Clamping strength t_{fix} [mm]	Admissible tension load in cracked concrete C20/25 [kN]	Admissible tension load in non-cracked concrete C20/25 [kN]	Recommended tension load in uncracked concrete C20/25 ⁴⁾ [kN]
5 x 30 ¹⁾	T-20	7.9	4	35	30	1	-	-	1.9
5 x 50 ¹⁾	T-20	7.9	4	40	35	15	-	-	2.6
6 x 30 ¹⁾	T-30	11.6	5	35	30	1	-	-	1.9
6 x 40 ¹⁾	T-30	11.6	5	40	35	5	-	-	2.4
6 x 50	T-30	11.6	5	55	45	5	0.3 ²⁾	1.5 ²⁾	3.8
6 x 60	T-30	11.6	5	55	45	15	0.3 ²⁾	1.5 ²⁾	3.8
6 x 80	T-30	11.6	5	55	45	35	0.3 ²⁾	1.5 ²⁾	3.8
7.5 x 25 ¹⁾	T-40	13.6	6	30	25	1	-	-	1.2
7.5 x 45	T-40	13.6	6	55	45	1	0.5 ²⁾	2.0 ²⁾	3.7
7.5 x 50	T-40	13.6	6	55	45	5	0.5 ²⁾	2.0 ²⁾	3.7
7.5 x 70	T-40	13.6	6	65	55	15	2.0 ³⁾	3.1 ³⁾	5.3
10 x 70	T-40	17	8	75	65	5	3.7 ³⁾	4.9 ³⁾	6.8

1) = not a component of the approvals 2) = in acc. with DIBt approval no. Z-21.1-1503 3) = in acc. with ETA 05/0010 4) = manufacturer specification for use without approval