



## Dimensions for screws and bolts

Note: When inquiring about 5 digit part numbers beginning with 8, please preface the number with R264-. Example: 88111 should be R264-88111.

### Other screws with metric thread

R264 - article	Dimensions	M 4	M 5	M 6	M 8	
<b>88138</b> straight screw hooks type 4E		h	10	12	14	18
	d	3.5	4.4	5.2	7	
	l	40	50	60	60	
	l <sub>1</sub>	25	35	45	45	
	F <sub>max</sub>	12.5 kg	20 kg	35 kg	50 kg	

R264 - article	Dimensions	M 4	M 5	M 6	M 8	
<b>88142</b> cup hooks type 11 E		w	12 / 16	16	18	22
	d	3.5	4.4	5.2	7.0	
	l	40 / 50	50 / 60	50 / 60	70 / 80	
	l <sub>1</sub>	20 / 25	23 / 30	20 / 30	32 / 42	
	F <sub>max</sub>	9 kg	12.50 kg	25 kg	40 kg	

R264 - article	Dimensions	M 10	M 12	M 12	
<b>88145</b> heavy duty screw eyes type 18E		w	22	22	22
	d	8.9	10.6	10.6	
	l	120 / 140	160	180	
	l <sub>1</sub>	73	93	115	
	F <sub>max</sub>	125 kg	175 kg	175 kg	

### Slotted and cross recessed screws with metric thread

DIN (ISO)	Dimensions	M 2	M 2.5	M 3	M 4	M 5	M 6	M 8	M 10	
<b>84</b> (1207)		dk	3.8	4.5	5.5	7	8.5	10	13	16
	k	1.3	1.6	2	2.6	3.3	3.9	5	6	
	n	0.5	0.6	0.8	1.2	1.2	1.6	2	2.5	
	b	25	25	25	38	38	38	38	38	

DIN	Dimensions	M 2	M 2.5	M 3	M 4	M 5	M 6	M 8	M 10	
<b>85</b> (1580) *) acc. to ISO 1580		dk	4*	5*	6	8	10	12	16	20
	k	1.3*	1.5*	1.8	2.4	3	3.6	4.8	6	
	n	0.5*	0.6*	0.8	1.2	1.1	1.6	2	2.5	
	b	25*	25*	25	38	38	38	38	38	

DIN	Dimensions	M 3	M 4	M 5	M 6	M 8	M 10	
<b>920</b>		a <sub>max</sub>	1	1.4	1.6	2	3	
	dk	4	5.5	6.5	8	10	13	
<b>921</b>		k	1.8	2.4	2.7	3.1	3.8	4,60,5
	n	0.5	0.6	0.8	1	1.2	1.6	
	t <sub>max</sub>	1.15	1.5	1.6	1.9	2.4	2.8	

DIN	Dimensions	M 3	M 4	M 5	M 6	M 8	M 10
<b>923</b>		dk	7	8.5	11	13	20
	k	1.8	2.4	2.7	3.1	3.8	4.6
	b	4.5	6	7	9	11	13.5
	ds	4	5.5	7	8	10	13

DIN	Dimensions	M 3	M 4	M 5	M 6	M 8	
<b>927</b>		dk	4	5.5	6.5	8	10
	b	4.5	6	7	8	11	
	n	0.5	0.6	0.8	1	1.2	
	t <sub>max</sub>	1.05	1.42	1.63	2.0	1.9	