



Dimensions for pins

Parallel pins

DIN (ISO)	Dimensions	0.8	1	1.5	2	2.5	3
7	$C_{max\ DIN}$	0.12	0.15	0.23	0.30	0.4	0.45
	$C_{max\ ISO}$	0.16	0.20	0.30	0.35	0.4	0.50
	r	0.8	1	1.6	2	2.5	3
(2338)	Dimensions	4	5	6	8	10	12
	$C_{max\ DIN}$	0.60	0.75	0.9	1.2	1.5	1.8
	$C_{max\ ISO}$	0.63	0.80	1.2	1.6	2.0	2.5
	Dimensions	13 *	14	16	20	25	30
	$C_{max\ DIN}$	1.9	2	2.5	3.0	4	4.5
	$C_{max\ ISO}$	-	-	3.0	3.5	4	5.0
	r	14	16	16	20	25	32

d = nominal size
 * intermediate sizes not included in the standard

DIN (ISO)	Dimensions	1	1.5	2	2.5	3	4	5
6325	l_2	0.4	0.5	0.6	0.7	0.8	1	1.2
	r	1	1.6	2	2.5	3	4	5
	z_1	0.15	0.23	0.3	0.4	0.45	0.6	0.75
	z_2	0.08	0.12	0.18	0.25	0.3	0.4	0.5
	c	0.2	0.3	0.35	0.4	0.5	0.63	0.98
(8734)	Dimensions	6	8	10	12	14	16	20
	l_2	1.5	1.8	2	2.5	2.5	3	4
	r	6	8	10	12	16	16	20
	z_1	0.9	1.2	1.5	1.8	2	2.5	3
	z_2	0.6	0.8	1	1.3	1.3	1.7	2
	c	1.2	1.6	2	2.5	-	3	3.5

d = nominal size

DIN	Dimensions	4 *	5 *	6	8	10	12
7979	a_2	0.5	0.6	0.8	1	1.2	1.6
	c_1	0.4	0.5	0.6	0.8	1	1.2
	c_2	1.3	1.7	2.1	2.6	3	3.8
	d_2	M 3	M 3	M 4	M 5	M 6	M 6
	t_1	6	6	6	8	10	10
	$t_2\ min$	7	7	10	12	16	16
		Dimensions	14	16	20	25	30
(8733)	a_2	1.8	2	2.5	3	4	5
	c_1	1.4	1.6	2	2.5	3	4
	c_2	4	4.7	6	6	7	8
	d_2	M 8	M 8	M10	M16	M20	M20
	t_1	12	12	16	24	30	30
	$t_2\ min$	20	20	25	34	42	42
	(8735)						

d_1 = nominal size
 * intermediate sizes not included in the standard

Taper pins

DIN (ISO)	Dimensions	1	1.5	2	2.5	3	4
1	$C_{max\ DIN}$	0.15	0.23	0.30	0.40	0.45	0.6
	a_{ISO}	0.12	0.20	0.25	0.30	0.40	0.5
(2339)	Dimensions	5	6	6.5 *	7 *	8	10
	$C_{max\ DIN}$	0.75	0.9	1	1.1	1.2	1.5
	a_{ISO}	0.63	0.8	0.8	0.9	1.0	1.2
	Dimensions	12	13 *	14	16	20	
	$C_{max\ DIN}$	1.8	1.9	2	2.5	3.0	
	a_{ISO}	1.6	1.7	1.8	2.0	2.5	

* intermediate sizes not included in the standard