



## Dimensions for handles





### Grips


DIN	Dimensions	M 6	M 8	M 10	M 12	M 16
<b>6336 D</b>  type D: with continuous thread	$d_1$	32	40	50	63	80
	$d_2$	12	14	18	20	25
	$d_5$	6.4	8.4	10.5	13	17
	$d_6$	26	34	42	52	64
	$h_1$	21	26	34	42	52
	$h_3$	10	13	17	21	25
	$t_2$	10	13	16	20	20

DIN	Dimensions	M 4	M 5	M 6	M 8	M 10	M 12	M 16
<b>6336 K</b>  type K: with threaded bush	$d_1$	20	25	32	40	50	63	80
	$d_6$	16	20	26	34	42	52	64
	$d_7$	10	12	14	18	22	26	35
	$h_3$	7	8	10	13	17	21	25
	$h_4$	13	16	20	25	32	40	50
	$t_{3min}$	6.5	9.5	12	14	18	22	30

### Tommy screws/Tommy nuts

DIN	Dimensions	M 6	M 8	M 10	M 12	M 16	M 20
<b>6304 E</b>  type E: without thrust pad thrust pads → DIN 6311	$l_1$	40/50	50/60	60/70	70/80	75/90/100	75/90/100
	$d_2$	12	14	18	20	24	30
	$d_3$	5	6	8	10	12	16
	$d_4$	4.5	6	8	8	12	15.5
	$d_5$	4	5.4	7.2	7.2	11	14.4
	$l_2$	10	12	14	18	20	28
	$l_3$	50	60	80	100	120	140
	$l_5$	30/40	35/45	40/50	50/60	55/70/90	55/70/90
	$l_6$	5	5	7	9	10	14
	$l_7$	6	7.5	9	10	12	14
$l_8$	2.5	3	4.5	4.5	5	5.5	

DIN	Dimensions	M 10	M 12	M 16	M 20
<b>6305</b> 	$d_2$	18	20	24	30
	$d_3$	8	10	12	16
	$l_1$	25	25	35	40
	$l_2$	60	70	85	95
	$l_3$	80	100	120	140
	$l_4$	7	9	11	14

DIN	Dimensions	M 10	M 12	M 16	M 20
<b>6307</b> 	$d_2$	18	20	24	30
	$d_3$	8	10	12	16
	$l_1$	25	25	35	40
	$l_2$	60	70	85	95
	$l_3$	80	100	120	140
	$l_4$	30	35	45	50
	$l_5$	7	9	11	14
	$t$	23	26	28	34