




## Product information: Cable ties

Note: When inquiring about 5 digit part numbers beginning with 8, please preface the number with R264-. Example: 88111 should be R264-88111.

### Cable tie mounts

R264 - article	Dimensions <sup>1)</sup>	5.4	
<b>82550 MB-CA</b> 	l	29	
	b	29	
	h	5.7	
	Fastening - Ø	4.2	
	Type <sup>2)</sup>	MB4CAS	
<b>82553 MB-A</b> 	<b>Dimensions <sup>1)</sup></b>	<b>5.4</b>	
	l	28	
	b <sub>1</sub>	28	
	h	4.7	
	b <sub>2</sub>	20.2	
	Fastening - Ø	4.0	
	Type <sup>2)</sup>	MB4A	
	<b>Version</b>	<b>MB - CA and MB - A</b>	
	Material	Polyamide 6.6 (PA66), HF = halogen free	
	Colour	NA = nature	
Properties	Operating temperature: -40 °C to 85 °C for 5,000 h, short-term 105 °C (500 h) <sup>3)</sup>		
Fastening	CA = self-adhesive/A = self-adhesive + threadable		

<sup>1)</sup> cable tie width = nominal size  
<sup>2)</sup> type name = HellermannTyton  
<sup>3)</sup> flammability acc. to UL 94 V2 (without adhesive)

R264 - article	Dimensions	8.0
<b>82560 CL8</b> 	l	27.3
	b	12.5
	h <sub>1</sub>	16.0
	h <sub>2</sub>	5.0
	Fastening - Ø	6.5
Type <sup>1)</sup>	CL8	
<b>Version</b>	<b>CL8</b>	
Material	Polyamide 6.6 (PA66), HF = halogen free	
Colour	NA = nature	
Properties	Operating temperature: -40 °C to 85 °C for 5,000 h, short-term 105 °C (500 h) <sup>3)</sup>	
Fastening	threadable	

<sup>1)</sup> cable tie width = nominal size  
<sup>2)</sup> type name = HellermannTyton  
<sup>3)</sup> flammability acc. to UL 94 V2