

NORBAR torque wrench

Robust industrial wrench with the highest precision.
 Release by gentle and rebound-free snapping of the shaft.
 Overloading of fasteners impossible.
 Durable ratchet head with right/left operation.
 Simple adjustment using the scale in Nm and Lb/ft
 at the end of the handle.



Net price per item

Type		500	700	1000	1500
Range	min. Nm	100	150	300	700
	max. Nm	500	700	1000	1500
Drive	inch	3/4	3/4	3/4	3/4
Length	mm	915	1090	1470	1470
Weight	kg	5,2	6,3	7,3	10,4
Price		540.–	555.–	580.–	830.–

NORBAR torque amplifier

For high moments of torque, ball-bearing mounted planetary gearing with low, compensated friction, ensuring precise adherence to the amplification ratio, with reaction-plate to trap the counter-forces.
 Type 5/25 and 7/25 with return stop.



Net price per item

Type		HT 3	HT 3 hd	5/25	7/25	
Maximum load	output	Nm	1300	2700	3400	6000
	input	Nm	260	540	136	240
Inside square	input	inch	1/2	3/4	1/2	3/4
Outside square	input	inch	3/4	1	1 1/2	1 1/2
Ratio			1:5	1:5	1:25	1:25
Diameter	mm		108	108	119	144
Height	mm		120	129	190	226
Weight	kg		3,1	3,2	11,0	17,0
Price			1120.–	1120.–	3580.–	4210.–