


**RAMPA Connecting Nuts type TXV**  
with combi slot are applied together with RAMPA Connecting Screws type TXS (p. 39). This application is employed when positioning e.g. attached wall cabinets.  
Borehole: 8,0 mm


**RAMPA Connecting Nuts type TXVR**  
with combi slot are applied together with RAMPA Connecting Screws type TXSR (p. 39). This application is employed when positioning e.g. attached wall cabinets.  
Borehole: 5,0 mm

XXX = available from stock

Type TXV Article No.	Head Ø	Shank Ø	Length	Internal Thread	Kilos per 1000	Steel nickel plated
144 615 003	15	8	15	M 6	4,0	XXX
144 625 003	15	8	25	M 6	8,0	XXX
144 631 003	15	8	31	M 6	10,2	XXX
144 638 003	15	8	38	M 6	15,0	XXX




RAMPA Connecting Nuts  
type TXV



RAMPA Connecting Nuts  
type TXVR

XXX = available from stock

Type TXVR Article No.	Head Ø	Shank Ø	Length	Internal Thread	Kilos per 1000	Steel nickel plated
146 415 003	10	5	15	M 4	2,0	XXX
146 420 003	10	5	20	M 4	2,5	XXX
146 425 003	10	5	25	M 4	3,0	XXX
146 427 003	10	5	27	M 4	3,4	XXX
146 430 003	10	5	30	M 4	4,0	XXX
146 435 003	10	5	35	M 4	4,5	XXX



Matching RAMPA Screws for this connection