

RAMPA Knob Screws type TXM have a combi slot. They are applied to join furniture knobs and handles.

RAMPA Connecting Screws type TXS with combi slot are applied together with RAMPA Connecting Nuts type TXV (p. 25). This application is employed when positioning e.g. attached wall cabinets.
Borehole: 8,0 mm

RAMPA Connectings Screws type TXSR with combi slot are applied together with RAMPA Connecting Nuts type TXVR (p. 25). This application is employed when positioning e.g. attached wall cabinets.
Borehole: 5,0 mm.

Maryland Metrics
<http://mdmetric.com>

Type TXM Article No.	Dimension	Kilos per 1000	Steel zinc plated
143 410 001	M 4 x 10	1,4	XXX
143 415 001	M 4 x 15	1,8	XXX
143 420 001	M 4 x 20	2,1	XXX
143 422 501	M 4 x 22,5	2,3	XXX
143 425 001	M 4 x 25	2,5	XXX
143 430 001	M 4 x 30	2,9	XXX
143 435 001	M 4 x 35	3,2	XXX
143 445 001	M 4 x 45	3,9	XXX


XXX = available from stock



RAMPA
Knob Screws type TXM

Type TXS Article No.	Dimension	Kilos per 1000	Steel nickel plated
145 614 003	M 6 x 14	5,5	XXX
145 620 003	M 6 x 20	6,0	XXX

XXX = available from stock




RAMPA
Connecting Screws type TXS

Type TXSR Article No.	Dimension	Kilos per 1000	Steel nickel plated
147 415 003	M 4 x 15	1,0	XXX
147 420 003	M 4 x 20	1,7	XXX
147 425 003	M 4 x 25	2,6	XXX

XXX = available from stock



RAMPA
Connectings Screws type TXSR



Matching RAMPA Connecting nuts for this application