



intelligent connection

SERTO Products are Nationally Distributed by:


MARYLAND METRICS

Phones: (410)358-3130 (800)638-1830

Faxes: (410)358-3142 (800)872-9329

P.O.Box 261 Owings Mills, MD 21117 USA

URL: <http://serto.net> Email: sales@serto.net




**Are you pouring
your money into
the sealing of
threads?**

Not with precoated threads!

You save time and money and get the highest quality*.
Production costs are reduced because there is one workstep less.
A test will pay off: order ready-to-assemble threads!

* The threads are precoated by machine with Loctite® 5061 thread sealant,
guaranteeing constant high quality.

Under tight control!



With precoated threads you obtain optimal sealing of tapered outside threads. The water-based, non-hardening, non-toxic sealing compound Loctite® 5061 is applied by machine. This assures that the sealing compound is applied evenly and directly at potential leakage points at the base and the flank of the thread, thus providing extreme leak-tightness and reliability. Precoated threads from SERTO may be used in a wide variety of applications.

- **Loctite® 5061 Dri-Seal® Sealing Compound**
 - **Ready for assembly**
 - **Easily adjustable**
 - **Environmentally friendly**
 - **Non-toxic, solvent-free**
 - **Heat resistance from -40 °C to +120 °C**
 - **Very good media resistance**
 - **Approved by: DVGW, KTW, SVGW**
 - **For brass, stainless steel and plastic unions**

Technical Data*

Chemical base	Polyacrylate, aqueous, non-hardening
Temperature	-40 °C to +120 °C
Pressure (PN)	16 bar, others possible
Adjustability	45° (DIN 30660)
Media	Air, oil, water (hot, cold)

Note: Loctite® 5061 is unsuitable for use with pure oxygen or steam. Further information can be obtained from your distributor.

*The data comes from the manufacturer of Loctite® 5061. These are subject to change without notice. Clarification of the suitability for use of coated threads from SERTO AG is the responsibility of the designer and must be carried out in advance. SERTO AG will accept no liability there after.

Your SERTO partner:

USA: Maryland Metrics, P.O. Box 261 Owings Mills, MD 21117,
Tel. (410)358-3130 (800)638-1830, Fax (410)358-3142 (800)872-9329
email: tech@serto.net web: <http://www.serto.net>

CH: SERTO AG, CH-8355 Aadorf, Tel. 052 3681111, Fax 052 3681112