



Capillary Tubing

STAINLESS STEEL 304, 316, 316L, 321, ASTM A213, ASTM A-269, DIN 17458 CLASS 1, DIN 2462-1

Tolerance: Permissible variations in OD +/- .005" (.13 mm), Wall Thickness +/- 15%

I.D. in mm, listed in center area.

O.D. mm	wall																												
	0.025	0.075	0.080	0.090	0.100	0.125	0.130	0.150	0.175	0.200	0.225	0.250	0.300	0.350	0.375	0.400	0.450	0.500	0.600	0.75	0.80	0.85	1.00	1.25	1.50	2.00	2.50		
0.10	0.05																												
0.20			0.04																										
0.30		0.15	0.14		0.10																								
0.40					0.20																								
0.50					0.30			0.20																					
0.55				0.37																									
0.60					0.40		0.34																						
0.62								0.32																					
0.70						0.45		0.40																					
0.80							0.50	0.45			0.30		0.10																
0.90									0.50																				
1.00					0.80		0.70		0.60		0.50	0.40	0.30																
1.10									0.70																				
1.20									0.80								0.30												
1.30										0.85	0.80																		
1.40									1.00																				
1.50							1.20		1.10		1.00		0.80		0.70		0.50												
1.60									1.20			1.00					0.60		0.10										
1.70									1.30																				
1.80												1.30			1.00														
1.90												1.40																	
2.00					1.80				1.60		1.50	1.40					1.00												
2.20												1.60										0.50							
2.40															1.60														
2.50									2.10		2.00	1.90			1.70		1.50												
2.60												2.00																	
2.80															2.00														
3.00									2.60		2.50						2.00		1.50				1.00						
3.20									2.80						2.40														
3.25																													
3.50														2.75			2.50	2.30											
4.00											3.50						3.00	2.50					2.00	1.50	1.00				
4.50											4.00						3.50												
5.00							4.70		4.60		4.50						4.00	3.50				3.00		2.00					
5.30											4.80																		
5.50																								3.50					
6.00							5.70				5.50				5.20		5.00	4.50	4.40			4.00		3.00	2.00	1.00			